FORMAT: USA MATERIAL SAFETY DATA SHEET

PRODUCT: GE286 ALMOND BATH SILICONE II

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: SUPPLIED BY:

GE SILICONES GE SILICONES

260 HUDSON RIVER ROAD 260 HUDSON RIVER ROAD

WATERFORD, NY 12188 WATERFORD, NY 12188

EMERGENCY PHONE (24 HRS) EMERGENCY PHONE (24 HRS)

(518) 237-3330 (518) 237-3330

REVISED: 01/29/03

PREPARER: JH MERRIFIELD

CHEMICAL FAMILY/USE: SILICONE RUBBER SEALANT

FORMULA: MIXTURE

2. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION/ APPROX. ACGIH TLV OSHA PEL

CAS REG NO. WGT. % TWA STEL TWA STEL UNITS

HAZARDOUS

METHYLTRIMETHOXYSILANE

1185-55-3 1-5 200(R) NE 200(R) NE PPM

HEXAMETHYLDISILAZANE

999-97-3 1-5 25(R) NE 35STEL NE (R) PPM

DISTILLATES, PETROLEUM, HYDROTREATED

LIGHT

64742-47-8 5-10 NE NA NE NA NA

2. NON-HAZARDOUS

ME-DIMETHOXY/STPD POLYDIME-SILOXANE

68037-58-1 30-60 NE NE NE NE NA

DIMETHYLPOLYSILOXANE

63148-62-9 10-30 NE NA NE NA NA

TETRAMER TREATED FUMED SILICA

68583-49-3 10-30 10 NE 15 NE MG/M3

See Section 15 for description of any WHMIS Trade Secret(s).

3. HAZARDS IDENTIFICATION

WARNING!

May cause skin, eye, and stomach irritation.

Harmful if swallowed, inhaled, or absorbed through skin.

May cause central nervous system depression.

Refer to other MSDS sections for detailed information.

Ammonia odor

Translucent solid

POTENTIAL HEALTH EFFECTS:

INGESTION:

May cause stomach discomfort.

May be harmful if swallowed.

May cause central nervous system effects.

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Not an expected route of exposure.

SKIN CONTACT:

Uncured product contact will irritate lips, gums and tongue.

Uncured product contact may irritate the skin.

May cause mild skin irritation.

May be absorbed through skin and produce effects as listed

```
under "Ingestion".
INHALATION:
Causes mild respiratory irritation.
Applies only in uncured state.
May also cause other effects as listed under "Ingestion".
EYE CONTACT:
Uncured product contact irritates eyes.
May cause mild eye irritation.
MEDICAL CONDITIONS AGGRAVATED:
Pre-existing skin or respiratory diseases.
SUBCHRONIC (TARGET ORGAN) EFFECTS:
Central nervous system
Skin
CHRONIC EFFECTS/CARCINOGENICITY:
This product or one of its ingredients present 0.1% or more
is NOT listed as a carcinogen or suspected carcinogen by
NTP, IARC, or OSHA.
PRODUCTS/INGREDIENTS
This space reserved for special use.
PRINCIPLE ROUTES OF EXPOSURE:
Oral.
Dermal - skin.
Eyes.
Inhalation.
OTHER:
This product contains methylpolysiloxanes which can generate
formaldehyde at approximately 300 degrees Fahrenheit (150'C)
and above, in atmospheres which contain oxygen. Formaldehyde
is a skin and respiratory sensitizer, eye and throat irritant,
acute toxicant, and potential cancer hazard. An MSDS for
formaldehyde is available from GE Silicones.
```

4. FIRST AID MEASURES

INGESTION:

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN:

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

Get medical attention if irritation persists.

INHALATION:

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN:

None known.

5. FIRE FIGHTING MEASURES

FLASH POINT: NA (C) NA (F)

METHOD : NA

IGNITION TEMP : UNKN (C) UNKN (F)

FLAMMABLE LIMITS IN AIR - LOWER (%): NA FLAMMABLE LIMITS IN AIR - UPPER (%): NA

SENSITIVITY TO MECHANICAL IMPACT (Y/N): NO

SENSITIVITY TO STATIC DISCHARGE:

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA:

All standard firefighting media

SPECIAL FIREFIGHTING PROCEDURES:

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

1

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wipe, scrape or soak up in an inert material and put in a container for disposal.

Wash walking surfaces with detergent and water to reduce slipping hazard.

Wear proper protective equipment as specified in the protective equipment section.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container closed when not in use.

Avoid contact with skin and eyes.

Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation.

Use mechanical ventilation to stay below TLV of 25 ppm ammonia. Store away from heat, sources of ignition, and incompatibles.

Product releases methanol during application and curing.

Keep away from children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
ENGINEERING CONTROLS:
Showers.
Eyewash stations.
See "Ventilation" below.
RESPIRATORY PROTECTION:
If exposure limits are exceeded or respiratory irritation is
experienced, NIOSH/MSHA approved respiratory protection should
be worn. Supplied air respirators may be required for
non-routine or emergency situations. Respiratory protection
must be provided in accordance with OSHA regulations (see 29
CFR 1910.134).
PROTECTIVE GLOVES:
Cloth gloves.
EYE AND FACE PROTECTION:
Safety glasses.
OTHER PROTECTIVE EQUIPMENT:
Wear eye protection and protective clothing.
VENTILATION:
Ventilation and other forms of engineering controls are
preferred for controlling exposures. Respiratory protection
may be needed for non-routine or emergency situations.
9. PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT INFORMATION:

BOILING POINT : NA (C) NA (F)

VAPOR PRESSURE(20 C)(MM HG): NA

VAPOR DENSITY (AIR=1) : NA

FREEZING POINT : NA (C) NA (F)

MELTING POINT : UNKN (C) UNKN (F)

PHYSICAL STATE : SOLID

ODOR : AMMONIA

COLOR : ALMOND

ODOR THRESHOLD (PPM) : 46.8

% VOLATILE BY VOLUME : NA

EVAP. RATE(BUTYL ACETATE=1): <1

SPECIFIC GRAVITY (WATER=1) : 1.035

DENSITY (KG/M3) : 1035

ACID/ALKALINITY (MEQ/G) : NA

PH : NA

VOC EXCL.H2O & EXEMPTS(G/L): 27

SOLUBILITY IN WATER (20 C) : INSOLUBLE

SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): PARTIALLY IN TOLUENE

10. STABILITY AND REACTIVITY

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS THERMAL DECOMPOSITION/COMBUSTION PRODUCTS:

Carbon monoxide.

Carbon dioxide.

Silicon dioxide.

Oxides of nitrogen.

 ${\tt Methanol.}$

Amines.

INCOMPATIBILITY (MATERIALS TO AVOID):

COPYRIGHT GENERAL ELECTRIC CO.

page: 7

```
None known.
CONDITIONS TO AVOID:
None known.
11. TOXICOLOGICAL INFORMATION
1
METHYLTRIMETHOXYSILANE
ACUTE ORAL LD50 (MG/KG): 12,500 (RAT)
ACUTE DERMAL LD50 (MG/KG): >10,000 (RBT)
ACUTE INHALATION LC50 (MG/L):
                               NF
OTHER:
None.
AMES TEST:
HEXAMETHYLDISILAZANE
ACUTE ORAL LD50 (MG/KG): 1000 RAT
ACUTE DERMAL LD50 (MG/KG): 540 RBT
ACUTE INHALATION LC50 (MG/L): NONE FOUND
OTHER:
Tested for severe skin irritation and mild eye irritation.
AMES TEST:
DISTILLATES, PETROLEUM, HYDROTREATED
ACUTE ORAL LD50 (MG/KG):
ACUTE DERMAL LD50 (MG/KG):
ACUTE INHALATION LC50 (MG/L):
OTHER:
AMES TEST:
```

ME-DIMETHOXY/STPD POLYDIME-SILOXANE

ACUTE ORAL LD50 (MG/KG): NA
ACUTE DERMAL LD50 (MG/KG): NA
ACUTE INHALATION LC50 (MG/L): NA
OTHER:
None.
AMES TEST:
DIMETHYLPOLYSILOXANE
ACUTE ORAL LD50 (MG/KG): >40000 MG/KG
ACUTE DERMAL LD50 (MG/KG): NONE
ACUTE INHALATION LC50 (MG/L): >535 MG/L
OTHER:
None.
AMES TEST:
TETRAMER TREATED FUMED SILICA
ACUTE DEBMAL LDEG (MG/KG): NA
ACUTE DERMAL LD50 (MG/KG): NA
ACUTE INHALATION LC50 (MG/L): NA
OTHER:
None.
AMES TEST:
1101.
12. ECOLOGICAL INFORMATION
ECOTOXICOLOGICAL INFORMATION: No data at this time
CHEMICAL FATE INFORMATION: No data at this time

13. DISPOSAL CONSIDERATIONS
DISPOSAL METHOD:
Disposal should be made in accordance with federal, state and
local regulations.
14. TRANSPORT INFORMATION
DOT SHIPPING NAME: NONE
DOT HAZARD CLASS: NOT DOT REGULATED
DOT LABEL(S): NONE
UN/NA NUMBER: NONE
PLACARDS: NONE
IATA:
NOT REGULATED BY IATA
IMO IMDG-code: NOT REGULATED FOR OCEAN TRANSPORTATION
EMS No: NA
EUROPEAN CLASS:
RID (OCTI): NONE
ADR (ECE) : NONE
RAR (IATA): NONE
15. REGULATORY INFORMATION
SARA SECTION 302:

SARA (311,312) HAZARD CLASS:

None Found

ACUTE HEALTH HAZARD	
NONE	
SARA (313) CHEMICALS:	
NONE	
CPSC CLASSIFICATION: NA	
NONE	
WHMIS HAZARD CLASS:	
D2A VERY TOXIC MATERIALS	
D2B TOXIC MATERIALS	
WHMIS TRADE SECRET:	
None	
EXPORT:	
SCHDLE B/HTSUS: 3214.10 Mastic Based on Rubber	
3206.49 Silicone Color Concentrate	
ECCN: EAR99	
EAR99	
HAZARD RATING SYSTEMS	
HMIS FLAMMABILITY 0 , REACTIVITY 0 , HEALTH 1	
FLAMMABILITY 0 , REACTIVITY 0 , HEALTH 0	
NFPA HEALTH = 1, FLAMMABILIITY = 0 , REACTIVITY = 0	
CALIFORNIA PROPOSITION 65:	
NONE	
16. OTHER INFORMATION	
This product or its components are on the European inventory of	
existing commercial chemicals (EINECS)	
These data are offered in good faith as typical values and not	

as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable.

However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. This product or its components are on the Australian inventory (ACOIN)..... C = ceiling limit NEGL = negligible EST= estimated NF = none found UNKN = unknown NA = not applicable ${\tt NE}$ = none established ${\tt REC}$ = recommended ND = none determined V = recomm. By vendor By-product = reaction by- SKN = skin product, TSCA inventory TS = trade secret status not required under R = recommended 40 CFR part 720.30(h-2) MST = mist STEL = short term exposure NT = not tested limit

*